PRODUCT CERTIFICATE

DURAN LUBRICANTS & CHEMICALS GmbH

ASTRON GREENMOL 10W-40

Modern Synthetic Technology • Molybden • NANO FILM™

Properties

ASTRON GREENMOL 10W-40 is a high-performance low-friction engine oil that reliably prevents deposits, reduces friction, and provides optimal wear protection for the engine — thanks to advanced ad-ditive technology, carefully selected base oils, and special additives.
These characteristics not only contribute to fuel savings but also help extend the engine's service life in the long term.

ASTRON GREENMOL 10W-40 delivers reliable performance under all operating conditions. It ensures consistently optimal oil pressure, provides high lubrication reliability, and remains stable even during extended service intervals.
In addition, it offers excellent wear protection, outstanding low-temperature behavior, and contributes to fuel savings as well as reduced emissions.

Application notes

ASTRON GREENMOL 10W-40 is ideally suited for modern gasoline and diesel engines, both with and without exhaust turbochargers. It provides reliable engine protection during extended oil change intervals and under high mechanical stress.

Observe manufacturer's instructions!

Service description

Speci ication:
- ACEA A3 / B4
- API SN

Recommendation*:
- Fiat 9.55535-G2
- GWM
- HAVAL
- MB 229.3
- Peugeot Citroen (PSA) B71 2300
- Renault RN 0700 / RN 0710
- VW 501 01 / 502 00 / 505 00
- Wuling

Duran Lubricants & Chemicals GmbH
Rodderheide 3–7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment – information is provided for products in the relevant Safety Data Sheet.

MADE IN GERMANY

PRODUCT CERTIFICATE

DURAN LUBRICANTS & CHEMICALS GmbH

ASTRON GREENMOL 10W-40

TYPICAL PARAMETERS	METHODS	UNITS	ASTRON GREENMOL 10W-40
Density at 15 °C	DIN 51 757	kg/m³	856
Appearance		-	green, fluorescent
Kinematic Viscosity at 40 °C	DIN 51 562	mm²/s	95
Kinematic Viscosity at 100 °C	DIN 51 562	mm²/s	14.2
Viscosity Index (VI)	DIN ISO 2909	-	154
Dynamic Viscosity at -25 °C	ASTM D5293	mPa·s	6580
Flash Point	DIN IS0 2592	°C	220
TBN (Total Base Number)	DIN ISO 3771	mg KOH/g	11
Pour Point	DIN ISO 3016	°C	-39

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

06.11.2025 / Vers. 1.0

Duran Lubricants & Chemicals GmbH
Rodderheide 3–7 • D-33824 Werther

Tel. +49 5203 901510
www.astron-oil.de
info@duran-oil.com

Health, Safety and Environment – information is provided for products in the relevant Safety Data Sheet.

MADE IN GERMANY